



POTENTIAL CONTRIBUTION FOR LEED® CANADA FOR HOMES 2009 REQUIREMENTS

INNOVATION AND DESIGN PROCESS (ID)

CREDITS DURABLE STRATEGIES POTENTIAL POINTS CREDIT RELE-

ID 3.1	Innovative or regional design	1-4 points	Direct
--------	-------------------------------	------------	--------

CONTRIBUTION AND COMPLIANCE* REGULAR SHEATHING

COMMENTS

Requirements

Prepare a written Innovative Design Request, to be submitted by the *LEED Canada for Homes* Provider to the CaGBC, explaining the merits of the proposed measure. This point should not be counted until *LEED Canada for Homes* has ruled on the request.

This credit rewards innovative or regional measures that are not addressed elsewhere in the Rating System. A project can also receive **1 LEED point** for exceeding the performance requirements of existing credits.

Exemplary performance requirement MR 2.2: Recycled content

Innovation and exemplary performance if the project reaches **30%** or more of recycled content.

Exemplary performance requirement MR 2.2: Regional materials

Innovation and exemplary performance if the project reaches **40%** or more of regional material.

The **REGULAR** sheathing from **BUILDING PRODUCTS OF CANADA CORP.** is a rigid panel produced from non-toxic organic materials and natural wood fibers. The panel is asphalt coated on both sides, for greater weather resistance. The wood fiber sheathing panels have excellent water vapour permeance which allows interior water vapour to escape to the exterior and not be trapped within the wall cavity where it could cause damage.

The **REGULAR** sheathing contains a high pre-consumer and post-consumer recycled content as well as a high regional material percentage.

These characteristics may help achieve exemplary performances for the following credits:

MR 2.2: Recycled content

MR 2.2: Regional materials

ENERGY AND ATMOSPHERE (EA)

EA 1	Optimize Energy Performance	Up to 28 - 34 points Or up to 5 points Based on the selected options	Direct
------	-----------------------------	--	--------

COMMENTS

Requirements

Improve the overall energy performance of a home by meeting or exceeding the performance of ERS (EnerGuide) 76 or HERS 80.

Prerequisites

1.1 Meet performance of ERS 76 or HERS 80 (0 points, required).

Credits

1.2 **Exceptional Energy Performance in ERS (EnerGuide)** (maximum 28 points). Exceed the performance of **ERS 76**. Use table 151 below relating the EnerGuide Rating System (ERS) index to the appropriate number of LEED points. This path can also pursue **EA 8** and **EA 9** and must meet the prerequisites and satisfy the conditions and must comply with the Credit **EA 8.1 Lighting** requirements.

OR

1.2 **Exceptional Energy Performance in HERS** (maximum 34 points). Exceed the performance of **HERS 80**. Use the table 15b below relating the **Home Energy Standards (HERS) Index** to the appropriate number of LEED points.

There are two possible conformity paths in the Energy and Atmosphere category. If a project is allocated points for Credit **EA 1.2 (SCE)**, Credits **EA 2 to 6, 7.3** and **10** must be skipped. If a project is allocated points for Credit **EA 1.2 (HERS)**, Credits **EA 2 to 6, 7.3** and **8 to 10** must be skipped.

The **REGULAR** sheathing from **BUILDING PRODUCTS OF CANADA CORP.** is a rigid panel produced from non-toxic organic materials and natural wood fibers. The panel is asphalt coated on both sides, for greater weather resistance. The wood fiber sheathing panels have excellent water vapour permeance which allows interior water vapour to escape to the exterior and not be trapped within the wall cavity where it could cause damage.

The **REGULAR** sheathing contributes to prerequisite and credit **EA 1** because it improves the energy efficiency of a building by adding a thermal resistance of **R-3/inch**.

BUILDING PRODUCTS OF CANADA CORP. has all required documents regarding LEED® and can rapidly provide information for a specific project.





POTENTIAL CONTRIBUTION FOR LEED® CANADA FOR HOMES 2009 REQUIREMENTS

CREDITS	DURABLE STRATEGIES	POTENTIAL POINTS	CREDIT RELE-	CONTRIBUTION AND COMPLIANCE* REGULAR SHEATHING
---------	--------------------	------------------	--------------	---

EA 2

Insulation

2 points

Direct

COMMENTS

Requirements

Design and install insulation to minimize heat transfer and thermal bridging.

Prerequisites

2.1 Basic Insulation (0 points, required)

- a. Install insulation that meets or exceeds the **R-value** requirements listed in Chapter 6 of the **2004 International Energy Conservation Code** (Table 602.1) or the **local building codes**, whichever is the more stringent. Alternative wall and insulation systems, such as structural insulated panels (SIPs) and insulated concrete forms (ICFs), must demonstrate a comparable **R-value**, but thermal mass or infiltration effect cannot be included in the **R-value** calculation.
- b. Install insulation to meet the provincial or local standards. Installation must be verified by a **Green Rater** conducting a pre-drywall thermal bypass inspection.

2.2 Enhanced Insulation (2 points)

- a. Install insulation that exceeds the **R-value** requirements listed in Chapter 6 of the **2004 International Energy Conservation Code** (Table 602.1) or the **local building codes**, whichever is the more stringent by at least **20%**. Alternative wall and insulation systems, such as structural insulated panels (SIPs) and insulated concrete forms (ICFs), must demonstrate a comparable **R-value**, but thermal mass or infiltration effect cannot be included in the **R-value** calculation.
- b. Install insulation to meet grade 1 standards. Installation must be verified by a **Green Rater** conducting a pre-drywall thermal bypass inspection.

The **REGULAR** sheathing from **BUILDING PRODUCTS OF CANADA CORP.** is a rigid panel produced from non-toxic organic materials and natural wood fibers. The panel is asphalt coated on both sides, for greater weather resistance. The wood fiber sheathing panels have excellent water vapour permeance which allows interior water vapour to escape to the exterior and not be trapped within the wall cavity where it could cause damage.

The **REGULAR** sheathing contributes to Prerequisite and Credit **EA 2** because it improves the energy efficiency of a building by adding a thermal resistance of **R-3/inch**.

EA 3

Air Filtration

3 points

Direct

COMMENTS

Requirements

Minimize energy consumption caused by uncontrolled air leakage into and out of conditioned spaces.

Prerequisites

3.1 Reduce Envelope Leakage: Meet the air leakage requirements shown in table 17. The air leakage rate must be tested and verified by a **Green Rater**.

Credits

3.2 Greatly Reduced Envelope Leakage (2 points). Meet the air leakage requirements shown in table 17. The air leakage rate must be tested and verified by a **Green Rater**.

OR

3.3 Minimal Envelope Leakage (3 points). Meet the air leakage requirements shown in table 17. The air leakage rate must be tested and verified by a **Green Rater**.

The **REGULAR** sheathing from **BUILDING PRODUCTS OF CANADA CORP.** is a rigid panel produced from non-toxic organic materials and natural wood fibers. The panel is asphalt coated on both sides, for greater weather resistance. The wood fiber sheathing panels have excellent water vapour permeance which allows interior water vapour to escape to the exterior and not be trapped within the wall cavity where it could cause damage.

However, **BUILDING PRODUCTS OF CANADA CORP.** has no control over the on-site installation technique or on the products used to seal the openings.

ENERGY AND ATMOSPHERE (EA)

BUILDING PRODUCTS OF CANADA CORP. has all required documents regarding LEED® and can rapidly provide information for a specific project.





POTENTIAL CONTRIBUTION FOR LEED® CANADA FOR HOMES 2009 REQUIREMENTS

MATERIALS AND RESOURCES (MR)

CREDITS	DURABLE STRATEGIES	POTENTIAL POINTS	CREDIT RELE-	CONTRIBUTION AND COMPLIANCE* REGULAR SHEATHING									
MR 2.1	Environmentally preferable products: FSC-Certified Tropical Wood	(0) Required	Direct	<p>COMMENTS</p> <p>The REGULAR sheathing from BUILDING PRODUCTS OF CANADA CORP. can contribute to this Prerequisite since it does not contain tropical wood components.</p> <p>BUILDING PRODUCTS OF CANADA CORP. can provide a compliance letter for this prerequisite in a certified project.</p>									
<p>Requirements</p> <p>Prerequisites</p> <p>2.1: FSC-Certified Tropical Wood. Meet the following two requirements, as applicable:</p> <p>A) Provide all wood-product suppliers with a notice (see figure 6, below) containing all the following elements:</p> <ul style="list-style-type: none"> a statement that the builder's preference is to purchase products containing tropical wood only if it is FSC-Certified; a request for the country of manufacture of each products supplied; <i>and</i> a request for a list of FSC-Certified tropical wood products the vendor can supply. <p>B) If tropical wood is intentionally used (i.e., specified in purchasing documents), use only FSC-Certified tropical wood products. Reused or reclaimed materials are exempt.</p>													
MR 2.2	Environmentally preferable products: FSC-Certified wood	Does not contribute	Direct	<p>COMMENTS</p> <p>BUILDING PRODUCTS OF CANADA CORP. is FSC Mix Credit certified. Certificate code RA-COC-006310, FSC-C113184. Therefore, all of the BUILDING PRODUCTS OF CANADA CORP.'s products are made out of 100% controlled wood.</p> <p>FSC certified REGULAR sheathing can be provided upon special request and availability. This product may thus contribute to this Credit since it is made of 50.6% (Regular panel 7/16 inch) and 54.4% (Regular panel 1/2 inch) wood components.</p> <p>The percentages are calculated according Credit MR 2.2 and exclude the post-consumer recycled content.</p> <p><i>All data relating to components with certified wood have been validated by a third party - Vertima inc.</i></p>									
<p>Requirements</p> <p>Use building component materials that meet one or more of the criteria below:</p> <p>Except as noted otherwise below, 90% of the component, as defined in each category, must meet the specification shown.</p> <p>Wood frame: 90% of wood used for the wall structure must be FSC certified.</p>													
MR 2.2	Environmentally preferable products: Recycled content	0.5 point by component	Direct	<p>COMMENTS</p> <p>The REGULAR sheathing can contribute to this Credit since it contains pre-consumer and post-consumer recycled content as shown in the table below:</p> <table border="1"> <thead> <tr> <th>Product</th> <th>Pre-consumer</th> <th>Post-consumer</th> </tr> </thead> <tbody> <tr> <td>Regular panel 7/16 inch</td> <td>43.9%</td> <td>37.3%</td> </tr> <tr> <td>Regular panel 1/2 inch</td> <td>47.7%</td> <td>35.5%</td> </tr> </tbody> </table> <p>Percentages of recycled content are calculated based on the total weight of the entire system and exclude the percentage of recycled content from internal waste of BUILDING PRODUCTS OF CANADA CORP. production as requested by LEED®.</p> <p><i>All data relating to components with recycled content were identified and validated by a third party - Vertima Inc.</i></p>	Product	Pre-consumer	Post-consumer	Regular panel 7/16 inch	43.9%	37.3%	Regular panel 1/2 inch	47.7%	35.5%
Product	Pre-consumer	Post-consumer											
Regular panel 7/16 inch	43.9%	37.3%											
Regular panel 1/2 inch	47.7%	35.5%											
<p>Requirements</p> <p>Environmentally preferable products 0.5 point each, maximum 8 points).</p> <p>Use building component materials that meet one or more of the criteria below. Except as noted in Table 24, a material must make up 90% of the component, by weight or volume. A single component that meets each criterion (i.e., environmentally preferable, low emissions, and local sourcing) can earn points for each.</p> <p>Roof, floor and walls—Insulation: must have 20% or more recycled content (0.5 point by components).</p>													
<p>BUILDING PRODUCTS OF CANADA CORP. has all required documents regarding LEED® and can rapidly provide information for a specific project</p>													





POTENTIAL CONTRIBUTION FOR LEED® CANADA FOR HOMES 2009 REQUIREMENTS

MATERIALS AND RESOURCES (MR)

CREDITS DURABLE STRATEGIES POTENTIAL POINTS CREDIT RELE- CONTRIBUTION AND COMPLIANCE* REGULAR SHEATHING

MR 2.2	Environmentally preferable products: Local production	0.5 point by component	Direct
--------	---	------------------------	--------

Requirements

Environmentally Preferable Products (0.5 point each, maximum of 8 points)

Use building materials that meet one or more of the criteria below. Except as noted in table 24, a material must make up **90%** of the component by weight or volume. A single component that meets each criterion (i.e., environmentally preferable, low emissions, and local sourcing) can earn points for each.

Local production

Use products that were extracted, processed, and manufactured within **800 km** (500 miles) of home if moved by truck or within **2,400 km** (1,500 miles) if moved by rail.

Except as noted otherwise below, **90%** of the component, as defined in each category, must meet the specification shown.

MR 2.2	Environmentally preferable products: Low emissions	0.5 point by component	Direct
--------	--	------------------------	--------

Requirements

Environmentally Preferable Products (0.5 point each, maximum of 8 points)

Use building materials that meet one or more of the criteria below. Except as noted in Table 24, a material must make up **90%** of the component by weight or volume. A single component that meets each criterion (i.e., environmentally preferable, low emissions, and local sourcing) can earn points for each.

Low emissions : Comply with California «Practice for Testing of VOCs from Building Materials Using Small Chambers» (www.dhs.ca.gov/ehlb/IAQ/VOCS/Practice.htm).

COMMENTS

The **REGULAR** sheathing can contribute to this Credit since some of the components used in its manufacturing are extracted, collected, treated and recovered within **800 km** or **2,400 km** (depending on the transportation mean used) of the final production site. The percentages of regional materials are shown in the table below:

Product	Regional materials
Regular panel 7/16 inch	81.2%
Regular panel 1/2 inch	83.2%

The percentage calculation was performed by considering the requirements of Credit MR 2.2 and the maximum distance radius (which depends on the means of transportation used).

The **REGULAR** sheathing is made in Pont-Rouge, QC, CAN (G3H 1S2).

The origin of the main components and the mean of transportation used must be validated for every project.

All data relating to regional materials have been validated by a third

COMMENTS

The **REGULAR** sheathing can contribute to this Credit since the components used in its manufacturing by **BUILDING PRODUCTS OF CANADA CORP.** comply with the low emissions requirements.

The **REGULAR** sheathing contains no volatile organic compound (VOC) and no added urea formaldehyde.

All data relating to emissions have been validated by a third party - Vertima inc.

BUILDING PRODUCTS OF CANADA CORP. has all required documents regarding LEED® and can rapidly provide information for a specific project



POINTS

TOTAL	UP TO 15.5 POINTS & UP TO 44.5 POINTS (BASED ON THE SELECTED OPTIONS)	The REGULAR panel can contribute up to a total of 15.5 points (prescriptive path) & 44.5 points (non-prescriptive path) for a LEED® Canada for Homes Project
--------------	--	---

** It is important to consider that the total amount of possible points reflects the number of achievable points in each credit categories. The product by itself cannot achieve this score, as defined above, but is considered as a beneficial element in order to achieve LEED® credits.*