



TECHNICAL DATA SHEET

WOOD FIBRE PAINTED PANELS

PRIMECOAT

DESCRIPTION:

Primecoat panel is a wood fibre panel with a factory applied of white paint that permits finishing without the need of a primer.

Primecoat panel is made from organic raw materials and is an environmentally friendly product.

USES:

Primecoat panels are used in residential, commercial or industrial applications on walls or for ceilings.

STORAGE AND MAINTENANCE:

Primecoat panels should be protected from the elements. Do not store directly on the ground.

Primecoat panels can be cleaned with a damp sponge, mild soap and lukewarm water.

SIZES AND PACKAGING

SKU	Dimensions	Panels/Bundle	Coverage/bundle	Bundles/Pallet
BLPRI	1219 x 2438 mm (48" x 96")	6	17.8 m ² (192 ft ²)	17
SKU	Dimensions	Coverage/Pallet	Panels/Pallet	
BLPRI110	1219 x 2438 mm (48" x 96")	327 m ² (3520 ft ²)	110	

CHARACTERISTICS	UNITS		RESULTS BP		REQUIREMENTS		TEST METHOD
	METRIC	IMPERIAL	METRIC	IMPERIAL	METRIC	IMPERIAL	
Nominal thickness	mm	in	Pass	Pass	11.1	0.4375	ASTM C209
Transverse Load at Rupture Min.	N	lbf	Pass	Pass	45	10.1	ASTM C209
Tensile Strength Parallel to Surface, Min.	kPa	psi	Pass	Pass	700	101	ASTM C209
Linear Moisture Expansion, Max.	%	%	Pass	Pass	0.5	0.5	ASTM D1037
Water Absorption Max., 2 hours	%	%	Pass	Pass	10	10	ASTM C209
Surface Burning Characteristics (FSR)	-	-	Pass	Pass	220	220	ULC S102

APPLICABLE STANDARDS

CAN/ULC S706.1 Type II, Class 5