



TECHNICAL DATA SHEET

WOOD FIBRE PAINTED PANELS

PRIMECOAT US

DESCRIPTION:

Primecoat panel is a wood fibre panel with a factory applied of white paint that permits finishing without the need of a primer. **Primecoat** panel is made from organic raw materials and is an environmentally friendly product.

USES:

Primecoat panels are used in residential, commercial or industrial applications on walls or for ceilings.

STORAGE AND MAINTENANCE:

Primecoat panels should be protected from the elements. Do not store directly on the ground.

Primecoat panels can be cleaned with a damp sponge, mild soap and lukewarm water.

SIZES AND PACKAGING

SKU	Dimensions	Panels/Bundle	Coverage/bundle	Bundles/Pallet
BLPRI5US	1219 x 2438 mm (48" x 96")	6	17.8 m ² (192 ft ²)	16
SKU	Dimensions	Coverage/Pallet	Panels/Pallet	
BLPRI5US96	1219 x 2438 mm (48" x 96")	285.3 m ² (3072 ft ²)	96	

CHARACTERISTICS	UNITS		RESULTS BP		REQUIREMENTS		TEST METHOD
	METRIC	IMPERIAL	METRIC	IMPERIAL	METRIC	IMPERIAL	
Nominal Thickness	mm	in	Pass	Pass	12.5	0.5	ASTM C209
Thermal Conductivity Max.	W(m·K)	Btu·in / (h·ft ² ·°F)	Pass	Pass	0.055	0.38	ASTM C209
Moisture Content, Max.	%	%	6	6	10	10	ASTM D1037
Transverse Load at Rupture Min.	N	lbf	46.7	10.5	46.7	10.5	ASTM C209
Tensile Strength Parallel to Surface, Min.	kPa	lbf/in ²	Pass	Pass	1034	150	ASTM C209
Linear Moisture Expansion, Max.	%	%	Pass	Pass	0.5	0.5	ASTM D1037

APPLICABLE STANDARDS

N/A