

BUILDING PRODUCTS OF CANADA CORP.

SINCE 1905

BP PRODECK

- PRODECK is a roof underlayment made from a woven polypropylene scrim coated on two sides. The coatings procure extra anti-skid performance and resistance to UV degradation.
- PRODECK is lightweight (21 lb per roll) and its built-in technology makes it highly tear-resistant.
- PRODECK covers 1 000 ft² per roll. It comes with a 15-year warranty against manufacturing defects and can be left exposed for 30 days.
- PRODECK can be installed under asphalt shingles, metal roofing, slate and shake roofing materials.
- PRODECK is part of the family of products eligible for the BP Weather-Tite™ Roofing System Warranty.





PRODECK IS LINED EVERY 2 INCHES TO FACILITATE THE INSTALLATION OF BP 6-INCH EXPOSURE SHINGLES;

(MYSTIQUE 42, VANGARD 42 IR and EVEREST 42 [East only]).

PHYSICAL PROPERTIES	
Width	1.2 m (48 in)
Length	76.2 m (250 ft)
Surface /roll	92.9 m² (1000 ft²)
Rolls / Pallet	49

APPLICABLES STANDARDS
ICC-ES AC 188 - CCRR-1105
ASTM D4869 for Type I, II, III and IV
ASTM D226 for Type I and II
CSA A123.3-05(10) for Type 1, 2 and 3

